

STAINLESS STEEL INTEGRATED TACTILE PLATE (300X600MM)

**P5
GRIP**

PRODUCT CODE: AT 219

RANGE	Integrated Tactile
DESIGN	Classic
MATERIAL	316 marine grade stainless steel
LOCATION	Indoor or Outdoor
DIMENSIONS	H300 x W600mm

FEATURES & BENEFITS

Machined, concentric circle design on the horizontal face with a smooth outer edge, tactiles are affixed to a solid plate as a single complete unit

Complies with the NCC [D4D9 Tactile Indicators] and Disability (Access to Premises—Buildings) standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

Identifiable by the unique “double lip” design, providing a distinct advantage when it comes to high slip resistance

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS 4586 APPENDIX A: Wet Pendulum Test
FOUR S 96 SLIDER	= 85 CLASS = P5
TRL 55 SLIDER	= 68 CLASS = P5

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the AT TGSI, see: AS/NZS 1428.4.1:2009.

TEST	AS/NZS 1428.4.1 APPENDIX E PARAGRAPH E3
LIGHT REFLECTANCE VALUE / WET	= 42.30
LIGHT REFLECTANCE VALUE / DRY	= 46.51

