

STAINLESS STEEL PVD BLACK WARNING TACTILE (SPIKED)

P5
GRIP

PRODUCT CODES: DESCRIPTION:

DT0122 SPIKED

RANGE	Warning Tactile
DESIGN	Classic
MATERIAL	316 marine grade stainless steel PVD
LOCATION	Indoor or outdoor
DIMENSIONS	OUTER DIA: 35mm TOP DIA: 25mm THICKNESS: 5mm



FEATURES & BENEFITS

Machined, concentric circle design on the horizontal face with a smooth outer edge

An environmentally friendly alternative to the solid classic tactile, featuring a cupped underside that uses less stainless steel putting less demand on resources

Complies with the NCC (D4D9 Tactile Indicators) and Disability (Access to Premises—Buildings) standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

Identifiable by the unique “double lip” design, providing a distinct advantage when it comes to high slip resistance

SLIP RESISTANCE TESTING


Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS 4586 APPENDIX A: Wet Pendulum Test
FOUR S 96 SLIDER	= 91 CLASS = P5
TRL 55 SLIDER	= 80 CLASS = P5

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the AT TGSI, see: AS/NZS 1428.4.1:2009.

TEST	AS/NZS 1428.4.1 APPENDIX E PARAGRAPH E3
LIGHT REFLECTANCE VALUE / WET	= 6.52
LIGHT REFLECTANCE VALUE / DRY	= 7.41



CODE	AT 215
FIXING	Drill and pressure fit (M8 x 25mm hole)